17.1 MATERIAL AND CONSTRUCTION REQUIREMENTS FOR CONCRETE AND GROUT

- 17.1.1 Materials and limitations on constituents
- 17.1.2 Specification and manufacture of concrete
- 17.1.3 Handling, placing and compacting of concrete
- 17.1.4 Finishing of unformed concrete surfaces
- 17.1.5 Curing and protection of concrete
- 17.1.5.1 Curing
- 17.1.5.2 Protection
- 17.1.6 Sampling and testing for compliance
- 17.1.6.1 General
- 17.1.6.2 Concrete specified by strength grade
- 17.1.6.3 Concrete specified by parameters other than strength grade
- 17.1.7 Rejection of concrete
- 17.1.7.1 Plastic concrete
- 17.1.7.2 Hardened concrete
- 17.1.7.3 Action on hardened concrete liable to rejection
- 17.1.8 Requirements for grout and grouting
- 17.1.8.1 Grout properties
- 17.1.8.2 Mixing and agitation

17.2 MATERIAL AND CONSTRUCTION REQUIREMENTS FOR REINFORCING STEEL

- 17.2.1 Materials
- 17.2.1.1 Reinforcement
- 17.2.1.2 Protective coatings
- 17.2.2 Fabrication
- 17.2.3 Bending
- 17.2.3.1 General
- 17.2.3.2 Internal diameter of bends or hooks
- 17.2.4 Surface condition
- 17.2.5 Fixing
- 17.2.6 Lightning protection by reinforcement

17.3 MATERIAL AND CONSTRUCTION REQUIREMENTS FOR PRESTRESSING DUCTS, ANCHORAGES AND TENDONS

- 17.3.1 Materials for ducts, anchorages and tendons
- 17.3.1.1 Ducts
- 17.3.1.2 Anchorages

17.3.1.3 Tendons 17.3.2 Construction requirements for ducts 17.3.2.1 Surface condition 17.3.2.2 Sealing 17.3.2.3 Fixing 17.3.3 Construction requirements for anchorages 17.3.3.1 Fixing 17.3.3.2 Surface condition 17.3.4 Construction requirements for tendons 17.3.4.1 Fabrication 17.3.4.2 Protection 17.3.4.3 Surface condition 17.3.4.4 Fixing 17.3.4.5 Tensioning 17.3.4.6 Maximum jacking forces 17.3.4.7 Grouting

17.3.5 Construction requirements for unbonded tendons

17.4 CONSTRUCTION REQUIREMENTS FOR JOINTS AND EMBEDDED ITEMS

- 17.4.1 Location of construction joints
- 17.4.2 Embedded and other items not shown in the drawings

17.5 TOLERANCES FOR STRUCTURES AND MEMBERS

- 17.5.1 General
- 17.5.2 Tolerances for position and size of structures and members
- 17.5.2.1 Absolute position
- 17.5.2.2 Floor-to-floor plumb
- 17.5.2.3 Deviation from specified dimensions
- 17.5.2.4 Deviation from surface alignment
- 17.5.3 Tolerance on position of reinforcement and tendons

17.6 FORMWORK

- 17.6.1 General
- 17.6.2 Stripping of forms and removal of formwork supports
- 17.6.2.1 General
- 17.6.2.2 Removal of formwork from vertical surfaces
- 17.6.2.3 Stripping of soffit forms from reinforced beams and slabs where control samples

are available

17.6.2.4 Stripping of soffit forms from reinforced slabs of normal-class concrete 17.6.2.5 Removal of formwork supports from reinforced members not supporting structures above

17.6.2.6 Removal of formwork supports from reinforced members in multistorey structures

17.6.2.7 Stripping of forms and removal of supports from soffits of prestressed concrete slabs and beams

17.6.2.8 Control tests